

**200 SERIES 2/2 NC DIRECT ACTING  
SOLENOID VALVE 1/4" NPT**



**TECHNICAL INFORMATION:**

MEDIA: COMPRESSED AIR, WATER, VACUUM, AND OTHER INERT GASES  
(FOR USE WITH OTHER MEDIA CONSULT CUSTOMER SERVICE.)

AMBIENT TEMPERATURE: -20 C TO +50 C

RELATIVE DUTY CYCLE: 100%

INSULATION CLASS: F (ACC. TO DIN VDE 580)

DEGREE OF PROTECTION: 1P65 (DUST TIGHT & WATER TIGHT)

**MATERIALS:**

ARMATURE TUBE: SPECIAL CUSTOM MADE CORROSION RESISTANT CR-NI-STEEL

PLUNGER : ELECTROLESS NICKEL PLATED STEEL

EPOXY MOLDED COIL

POWER CONSUMPTION: 15W DC & 22VA/50HZ - 19VA/60HZ

SEALS: VITON (DIAPHRAGM)

BODY: BRASS


STANDARD VOLTAGES: 110VAC, 220VAC, 12VDC, & 24VDC

VOLTAGE TOLERANCE: +/- 10%

FUNCTION	ORIFICE SIZE mm	PRESSURE PSI MAX.	FLOW FACTOR Cv	ADD VOLTAGE TO GET PART NUMBER EX: 214-110VAC
2/2 NC	2.3	AC-120 / DC-100	0.18	214-

NOTE: SHOWN WITH TYPE 2 DIN CONNECTORS  
(CONNECTOR MUST BE ORDERED SEPARTELY)

- COIL CAN BE ROTATED 360 DEGREES
- COIL CAN BE CHANGED UNDER PRESSURE
- FAST RESPONSE – DIRECT ACTING – SPRING RETURN
- PERFECT FOR LOW PRESSURE APPLICATION
- INSTALLATION: SLANT PIPE OR WATER LEVEL
- BRASS BODY



DIMENSIONS	A	B	C
IN MILLIMETERS	35.0	77.0	25.4